



Monos **ringo** ist eine LED Pendelleuchte mit einem nur 50 mm hohen und 20mm breiten Ring aus pulverbeschichtetem Aluminium. Die Lichtverteilung ist umlaufend ohne Unterbrechung zum Ringinneren gerichtet und mit einer opal/satinen Abdeckung versehen. Die filigrane Bauart lässt die Leuchte gleichsam im Raum schweben.


Lieferbar in Durchmessern von 432mm – 2000mm fügt sich die ringo, mit schlichter Eleganz, in jeden Raum. Die Pendelmontage, schräg oder exakt vertikal, erfolgt über höhenverstellbare Seilpendel. Der Treiber ist im Deckenbaldachin verbaut.



Monos **ringo** is a LED pendant luminaire with a ring of powder-coated aluminium that is only 50 mm high and 20 mm wide. The light distribution is directed without interruption to the inside of the ring and is covered with an opal/satin cover. The filigree design makes the luminaire seem to float in space.

Available in diameters from 432mm - 2000mm, the ringo fits into any room with simple elegance. The pendant mounting, diagonal or exactly vertical, is done with height-adjustable wire pendants. The driver is installed in the ceiling canopy.

RINGO



TECHNISCHE DATEN

Produktname / Product name	Ringo
Montageart / Mounting	Pendel / Suspended
Gehäuse / Housing	Aluminium
Gehäusefarbe / Color of Housing	RAL nach Wahl / RAL on request
Optik /Optic	Opal
Systemleistung / Systempower 1	63W/5229lm + 79W/6589lm + 93W/7739lm
Durchmesser / Diameters	432mm - 1974mm
Kelvin	2700, 3000, 4000, 6500
CRI	>80, >90
Lichtfarbtoleranz / Color tolerance	MacAdam 3 (3 SDCM)
Lebensdauer / Lifetime	>50.000h - L80/B10
Datenblatt Nr. / Data sheet No.	23.018D

TECHNICAL DATA