




TECHNISCHE DATEN

Produktname / Product name	Vision 625 L
Montageart / Mounting	Einlege / Laid In
Gehäuse / Housing	Aluminium
Gehäusefarbe / Color of Housing	RAL nach Wahl / RAL on request
Optik /Optic	Opal + Mikroprisma UGR<19
Lichtverteilung / Light distribution	direkt + direkt/indirekt
Systemleistung / Systempower 1	74W/9371lm
Durchmesser / Diameters	650mm x H: 182mm
Kelvin	2700, 3000, 4000, 6500
CRI	> 80, > 90
Lichtfarbtoleranz / Color tolerance	MacAdam 3 (3 SDCM)
Lebensdauer / Lifetime	>50.000h - L80/B10
Datenblatt Nr. / Data sheet No.	D25.001

TECHNICAL DATA



Monos vision 625, decorative luminaire for recessed mounting in M: 625 ceilings with visible profile. The basis of vision are round surface-mounted luminaires in various dimensions, mounted on a tapered recessed dome.

Light distribution purely direct or direct / indirect, available in RAL colour of choice as well as in special rusty optic. Arranged individually or in groups, the vision becomes a 3-dimensional furnishing object that architecturally enhances the ceiling.



monos
light in balance

www.monos.de